

## Product View

# Zaikai

## G-7500A



Android 14



64 Point Touch



Ai Inbuilt



Octa Core Chipset



MDM



K12 Educational Lifetime Content



Palm & Elbow Rejection



Google Assistant



128 GB Expandable upto 1TB



Surround Sound

## Specifications

| PANEL | SIZE           | RESPOND TIME           | VISUAL RATIO   | PANEL TYPE   | DISPLAY COLOURS     |
|-------|----------------|------------------------|----------------|--------------|---------------------|
|       | 75"            | <2.0ms                 | 16:09          | LCD/LED      | 1.07G(8BITS+FRC)    |
|       | FREQUENCY      | MAX VISUAL AREA        | RESOLUTION     | PIXEL PITCH  | COLOUR SATURABILITY |
|       | 60 Hz          | 1649.66(H)x927.93(V)mm | 3840x2160      |              | 70% NTSC            |
|       | BRIGHTNESS     | LIFE SPAN              | CONTRAST RATIO | LIGHT SOURCE | VIEW ANGLE          |
|       | 400cd/m2(±10%) | ≥50,000 Hr.            | 1200:01:00     | DLED         | LCD/LED             |

|  |   |   |   |   |
|--|---|---|---|---|
|  | - | - | - | - |
|  | - | - | - | - |

| AUDIO/VIDEO PARAMETERS | SPEAKERS | SOUND TRACK | POWER       | SUBWOOFER |
|------------------------|----------|-------------|-------------|-----------|
|                        |          | 2.1 CHANNEL | 15 X 2 WATT | 20 WATT   |

| TOUCH PARAMETERS | TOUCH SPECIFICATIONS                    | SUPPORT SYSTEM                                                 |                                | OUTPUT CO-ORDINATES |                |
|------------------|-----------------------------------------|----------------------------------------------------------------|--------------------------------|---------------------|----------------|
|                  | NON-CONTACT INFRARED SENSING TECHNOLOGY | WINDOWS 10/WINDOWS 8/WINDOWS 11 /ANDROID/LINUX/MAC OS X/CHROME |                                | 32767(W) x 32767(D) |                |
|                  | TOUCH POINTS                            | Min. IDENTIFIER                                                | WRITING DISPLAY                |                     | WRITING HEIGHT |
|                  | 64                                      | ≤2.0 mm                                                        | SINGLE STYLUS PEN 2 COLOR      |                     | MAX 400W       |
|                  | RESPOND TIME                            | TOUCH DEPTH                                                    | INPUT MODE                     |                     |                |
|                  | <2.0ms                                  | ±1mm(OVER 90% AREA)                                            | OPAQUE OBJECT(FINGURE,PEN etc) |                     |                |

| SYSTEM | VERSION      | CPU         | GPU               | RAM | ROM   |
|--------|--------------|-------------|-------------------|-----|-------|
|        | ANDROID 14.0 | A73*4+A53*4 | Mali-G52MP8 (8EE) | 8GB | 128GB |

| WIRELESS | BLUETOOTH | VERSION | WORKING FREQUENCY | WORKING DISTANCE | REMARK VIA |
|----------|-----------|---------|-------------------|------------------|------------|
|          |           | 5       | 2.4/5Ghz          | 10mtr            |            |
|          | WIFI      | VERSION | WORKING FREQUENCY | WORKING DISTANCE | REMARK VIA |
|          |           | 6       | 2.4/5Ghz          | 10mtr            |            |

| REAR I/O INTERFACE | HDMI IN  | USB2.0      | USB 3.0      | HDMI OUT | USB TOUCH PORT |
|--------------------|----------|-------------|--------------|----------|----------------|
|                    | 2        | 1           | 1            | 1        | 1              |
|                    | LINE OUT | OPTICAL OUT | LAN RJ 45 IN | TF CARD  | RS232          |
|                    | 1        | 1           | 1            | 1        | 1              |
|                    | -        | -           | -            | -        | MIC IN         |
|                    | -        | -           | -            | -        | 1              |

| FRONT INTERFACE | USB 3.0 | TOUCH USB | HDMI IN | TYPE C |
|-----------------|---------|-----------|---------|--------|
|                 | 2       | 1         | 1       | 1      |

| POWER | VOLTAGE               | MAX. POWER CONSUMPTION | STAND BY POWER CONSUMPTION |
|-------|-----------------------|------------------------|----------------------------|
|       | 100-240 AC 50/60Hz 4A | 280W                   | ≤0.5W                      |

| STRUCTURE | BARE DIMENSION         | PACKING DIMENSION   | MACHINE + WALL MOUNT THICKNESS    | VESA HOLE SITE |
|-----------|------------------------|---------------------|-----------------------------------|----------------|
|           | 1707 × 91.8 × 1022.7mm | 1873 × 270 × 1197mm | 118mm (W189060G)                  | 800 × 400mm    |
|           | NET WEIGHT             | GROSS WEIGHT        | WALL MOUNTING SCREW SPECIFICATION |                |
|           | 61.8KG                 | 81.3 KG             | M8 × 25mm                         |                |

| ENVIRONMENT | WORKING TEMPERATURE | WORKING HUMIDITY | STORAGE TEMPERATURE | STORAGE HUMIDITY | WORKING ELEVATION |
|-------------|---------------------|------------------|---------------------|------------------|-------------------|
|             | 0°C-40°C            | 10%-90%RH        | -20°C-60°C          | 10%-90%RH        | <5000m            |