

Product View

Zaikai

G-7500A



Android 14



64 Point Touch



AI inbuilt



Octa Core Chipset



MDM



K12 Educational Lifetime Content



Palm & Elbow Rejection



Google Assistant



128 GB Expandable upto 1TB



Surround Sound

Specifications

PANEL	SIZE	RESPOND TIME	VISUAL RATIO	PANEL TYPE	DISPLAY COLOURS
	75"	<2.0ms	16:09	LCD/LED	1.07G(8BITS+FRC)
	FREQUENCY	MAX VISUAL AREA	RESOLUTION	PROTECTIVE GLASS	COLOUR SATURABILITY
	60 Hz	1649.66(H)x927.93(V)mm	3840x2160	Toughened Anti-Glare	70% NTSC
	BRIGHTNESS	LIFE SPAN	CONTRAST RATIO	LIGHT SOURCE	VIEW ANGLE
	≥400 cd/m²	≥50,000 Hr.	1200:01:00	DLED	178° (H) / 178° (V)

OPTIONS	OPS	SCREEN SHARING	WHITEBOARD SOFTWARE
	OPS Compliant Expansion Slot	Wireless Screen Sharing Support	Yes

AUDIO/VIDEO PARAMETERS	SPEAKERS	SOUND TRACK	POWER	SUBWOOFER
		2.1 CHANNEL	15 X 2 WATT	20 WATT

TOUCH PARAMETERS	TOUCH SPECIFICATIONS	SUPPORT SYSTEM		OUTPUT CO-ORDINATES	
	NON-CONTACT INFRARED SENSING TECHNOLOGY	WINDOWS 10/WINDOWS 8/WINDOWS 11 /ANDROID/LINUX/MAC OS X/CHROME		32767(W) x 32767(D)	
	TOUCH POINTS	Min. IDENTIFIER	WRITING DISPLAY		WRITING HEIGHT
	64	≤2.0 mm	SINGLE STYLUS PEN 2 COLOR		MAX 400W
	RESPOND TIME	TOUCH DEPTH	INPUT MODE		
	<2.0ms	±1mm(OVER 90% AREA)	OPAQUE OBJECT(FINGURE,PEN etc)		

SYSTEM	VERSION	CPU	GPU	RAM	ROM
	ANDROID 14.0	A73*4+A53*4	Mali-G52MP8 (8EE)	8GB	128GB

WIRELESS	BLUETOOTH	VERSION	WORKING FREQUENCY	WORKING DISTANCE	REMARK VIA
		5	2.4/5Ghz	10mtr	
	WIFI	VERSION	WORKING FREQUENCY	WORKING DISTANCE	REMARK VIA
		6	2.4/5Ghz	10mtr	

REAR I/O INTERFACE	HDMI IN	USB2.0	USB 3.0	HDMI OUT	USB TOUCH PORT
	2	1	1	1	1
	LINE OUT	OPTICAL OUT	LAN RJ 45 IN	TF CARD	RS232
	1	1	1	1	1
	-	-	-	-	MIC IN
	-	-	-	-	1

FRONT INTERFACE	USB 3.0	TOUCH USB	HDMI IN	TYPE C
	2	1	1	1

POWER	VOLTAGE	MAX. POWER CONSUMPTION	STAND BY POWER CONSUMPTION
	100-240 AC 50/60Hz 4A	280W	≤0.5W

STRUCTURE	BARE DIMENSION	PACKING DIMENSION	MACHINE + WALL MOUNT THICKNESS	VESA HOLE SITE
	1707 × 91.8 × 1022.7mm	1873 × 270 × 1197mm	118mm (W189060G)	800 × 400mm
	NET WEIGHT	GROSS WEIGHT	WALL MOUNTING SCREW SPECIFICATION	
	61.8KG	81.3 KG	M8 × 25mm	

ENVIRONMENT	WORKING TEMPERATURE	WORKING HUMIDITY	STORAGE TEMPERATURE	STORAGE HUMIDITY	WORKING ELEVATION
	0°C~40°C	10%-90%RH	-20°C~60°C	10%-90%RH	<5000m